

Excel Single-phase Vertical Intelligent PDU (INT3) c/w 12x C13, 4x C19 sockets - 16A EN603...

Item Code: 555-1V-COM16-INT3-12C13-4C19-3B

excel
without compromise.



✕ Monitors overall voltage

✕ Local display via the RGB

✕ Embedded free software

✕ Choice of UK, Schuko, C13 and C19 socket types

✕ Horizontal and vertical options

✕ Individual socket monitoring and individual socket switching

Product Overview

The Excel Intelligent INT3 is designed to provide local and remote overall power monitoring as well as individual socket monitoring and switching, it is available with up to 48 sockets.

The Excel Intelligent INT3 can work as an individual master or run as a master and slave system. One master can have up to 31 slaves, all from one IP address, reducing the requirement for multiple IP addresses.

The Excel Intelligent INT3 comes with free software making it a highly competitive solution allowing the user to monitor and report on up to 50 IP addresses with the software. In theory it is possible to have up to 1600 PDU's each with up to 48 outlets per PDU, all from one free software licence.

Product Specifications

Feature	Values
Mounting direction	Vertical
Type of electric plug connection	16 Amp - EN6039 Style (BS4343)
Cable length	3 m
Number of C13 socket outlets	12
Number of C19 socket outlets	4
Supply voltage	230 V
SNMP	Yes
With display	Yes
Evaluation	Remote
With LED indication	Yes

Excel Single-phase Vertical Intelligent PDU (INT3) c/w 12x C13, 4x C19 sockets - 16A EN603...

Item Code: 555-1V-COM16-INT3-12C13-4C19-3B



With fuse	Yes
Ammeter	Yes
With temperature measurement	Yes
With mounting bracket	Yes

Additional specifications

Features	Values
Technology	Overall + individual socket monitoring + switching
Energy Metering	RMS Volts, RMS Amps, Kilowatts, Frequency, Power Factor
Metering per Input Line	Yes (overall and individual)
Metering per Output Receptacle	Yes
Remote Outlet Switching	Yes
Environmental port	Yes
Networking	SNMP (v1, 2, 3), HTML, HTTP, HTTPs, XML, Email Alerts
Remote Management	Yes
Daisy Chain	Yes (1 Master up to 31 Slaves)
Display	Local (remote display optional)
Environmental Sensors	Temperature Sensor Port (Up to 8 Sensors), Humidity / Temperature Sensor, Volt Free Contacts (3 Sets), Door Contacts, Electronic Door Handle, Card Reader / Pin Pads
Frequency	50 - 60 Hz
Main Input	85 - 265 VAC
Colour	Black (standard) - other colours available
Temperature Range	-10° to +50° C

Excel Single-phase Vertical Intelligent PDU (INT3) c/w 12x C13, 4x C19 sockets - 16A EN603...

Item Code: 555-1V-COM16-INT3-12C13-4C19-3B



Socket types



Standards

Applicable standard	Detail
RoHS	Restriction of Hazardous Substances - Compliant
IEC 60950-1	Information technology equipment - Safety

Part Number Table

Part Number	Description
555-1V-COM16-INT3-12C13-4C19-3B	Excel Single-phase Vertical Intelligent PDU (INT3) c/w 12x C13, 4x C19 sockets - 16A EN60309 3m Bottom-fed lead
555-1V-COM32-INT3-20SCH-XXX-3B	Excel Single-phase Vertical Intelligent PDU (INT3) c/w 20x Schuko sockets - 32A EN60309 3m Bottom-fed lead
555-1V-COM32-INT3-20UKL-XXX-3B	Excel Single-phase Vertical Intelligent PDU (INT3) c/w 20x UK Left sockets - 32A EN60309 3m Bottom-fed lead

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.