Excel 16-way Vertical PDU - 12x C13 + 4x C19 sockets, 32A IEC 60309 Plug

Item Code: 555-230







- X Choice of C13 and C19 sockets
- 3 metre PVC input lead is terminated with a 32 Amp rated IEC 60309 2P+E plug
- X CE compliant, RoHS complaint
- X 32A Master air circuit breake
- X External earth facility

Product Overview

Excel range of power distribution units are designed for installation and use within 19" networking cabinets and enclosures. Each unit comprises a high quality aluminium extruded housing into which are loaded up to 24 sockets.

The range of units are higher density vertical mounted with each unit fitted with a 32A master air circuit breaker and LED indicator to confirm power to the unit.

Product Specifications

Feature	Values
Mounting direction	Vertical
Electrical connection	Connecting cord with plug
Type of electric plug connection	32 Amp - EN6039 Style (BS4343)
Cable length	3 m
Number of C13 socket outlets	12
Number of C19 socket outlets	4
Length	1039 mm
Width	44.4 mm
Height	62 mm
Supply voltage	250 V
Surge Protected	Yes
With LED indication	Yes

Excel 16-way Vertical PDU - 12x C13 + 4x C19 sockets, 32A IEC 60309 Plug

Item Code: 555-230



With fuse	Yes
With mounting bracket	Yes

Standards

Applicable standard	Detail
RoHS	Restriction of Hazardous Substances - Compliant
BS 1363-2:1995	13 A plugs, socket-outlets, adaptors and connection units. Specification for 13 A switched and unswitched socket- outlets
IEC 60884-1:2002 + AMD1:2006 + AMD2:2013 CSV	Plugs and socket-outlets for household and similar purposes - Part1: General requirements

Part Number Table

Part Number	Description
555-230	Excel 16-way Vertical PDU - 12x C13 + 4x C19 sockets, 32A IEC 60309 Plug
555-231	Excel 20-way Vertical PDU - 16x C13 + 4x C19 sockets, 32A IEC 60309 Plug
555-232	Excel 24-way Vertical PDU - 20x C13 + 4x C19 sockets, 32A IEC 60309 Plug

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

